

Uralane[®] 5773 A/B Polyurethane Adhesive

Product Description

Uralane[®] 5773 A/B Polyurethane Adhesive is a two-part system which maintains high bond strength through 250°F (121°C). The adhesive forms tough, heat-resistant bonds between various metal substrates and other materials especially where different thermal expansion coefficients prevail.

Features

- High strength
- Tough, heat resistant

Typical Properties*

Property	Test Method	5773 A	5773 B	Mixed System
Appearance	Visual	Amber	Dark amber	Dark amber
Density, g/cm ³	ASTM D792	1.05	1.30	1.25
Viscosity at 25°C, cP	ASTM D2196	13,000	Semi-Paste	Semi-Paste

*Typical properties are based on Huntsman's test methods. Copies are available upon request.

Processing

Mix Ratio

Product	Parts by weight
Uralane [®] 5773 A Resin	100
Uralane [®] 5773 B Hardener	42

Mix both components thoroughly for several minutes to insure uniform blending. Material temperatures should be above 18°C when mixing. Avoid air entrapment while mixing.

Processing Data

Parameter	Value
Gel time, 50 g at 77°F (25°C), min	25 - 45
Typical cure cycles	Gel at 25°C + 16 hours at 66°C or
	5 - 7 days at 23°C

Typical Physical Properties

Unless otherwise stated, the data were determined with typical production batches using standard test methods. They are typical values only, and do not constitute a product specification.

Property	Test Method	Value
Tensile lap shear, Al-Al, psi (MPa) Unconditioned at -67°F (-55°C) at 77°F (25°C) at 250°F (121°C) After 30 days at 63°C /95% RH at 77°F (25°C) at 250°F (121°C)	ASTM D1002	3,000 (20.7) 2,500 (17.2) 900 (6.2) 2,500 (17.2) 700 (4.8)
T-peel, aluminum, pli (N/mm) Unconditioned After 30 days at 63°C /95% RH at 77°F (25°C)	ASTM D1876	35 (6.1) 35 (6.1)
Durometer hardness, Shore D Unconditioned After 30 days at 63°C /95% RH	ASTM D2240	50 50

Tested after Thermal Aging Exposure

Property	Initial	100 hours	500 hours	1000 hours
Tensile lap shear, Al-Al, psi (MPa) at -67°F (-55°C) at 77°F (25°C) at 250°F (121°C)	5,500 (37.9) 2,800 (19.3) 950 (6.5)	6,500 (44.8) 3,200 (22) 1,000 (6.9)	6,400 (44.1) 2,800 (19.3) 1,000 (6.9)	5,500 (37.9) 3,000 (20.6) 950 (6.5)
T-peel, pli (N/mm) at 77°F (25°C)	60 (10.5)	90 (15.7)	90 (15.7)	80 (14)

Storage

Uralane® 5773 A/B should be stored in a dry place, in the original sealed container at temperatures between 2°C and 40°C (36°F and 104°F). Under these storage conditions, and when supplied under Huntsman standard certification, the product has a shelf-life of **6 months** from date of manufacture (expiration date may differ based on customer specification). The product should not be exposed to direct sunlight.

These products are moisture sensitive and are packaged under a blanket of dry nitrogen. After opening a container, re-blanket with dry nitrogen and then tightly reseal.

Precautionary Statement

Huntsman Advanced Materials Americas LLC maintains up-to-date Safety Data Sheets (SDS) on all of its products. These sheets contain pertinent information that you may need to protect your employees and customers against any known health or safety hazards associated with our products. Users should review the latest MSDS to determine possible health hazards and appropriate precautions to implement prior to using this material.

First Aid!

Refer to SDS as mentioned above.

KEEP OUT OF REACH OF CHILDREN

FOR PROFESSIONAL AND INDUSTRIAL USE ONLY

Important Legal Notice

Sales of the product described herein ("Product") are subject to the general terms and conditions of sale of either Huntsman Advanced Materials LLC, or its appropriate affiliate including without limitation Huntsman Advanced Materials (Europe) BVBA, Huntsman Advanced Materials Americas Inc., or Huntsman Advanced Materials (Hong Kong) Ltd. ("Huntsman"). The following supercedes Buyer's documents.

Huntsman warrants that at the time and place of delivery all Products sold to Buyer shall conform to the specifications provided to Buyer by Huntsman.

While the information and recommendations included in this publication are, to the best of Huntsman's knowledge, accurate as of the date of publication, NOTHING CONTAINED HEREIN (EXCEPT AS SET FORTH ABOVE REGARDING CONFORMANCE WITH SPECIFICATIONS PROVIDED TO BUYER BY HUNTSMAN) IS TO BE CONSTRUED AS A REPRESENTATION OR WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, NONINFRINGEMENT OF ANY INTELLECTUAL PROPERTY RIGHTS, OR WARRANTIES AS TO QUALITY OR CORRESPONDENCE WITH PRIOR DESCRIPTION OR SAMPLE, AND THE BUYER ASSUMES ALL RISK AND LIABILITY WHATSOEVER RESULTING FROM THE USE OF SUCH PRODUCT, WHETHER USED SINGLY OR IN COMBINATION WITH OTHER SUBSTANCES.

No statements or recommendations made herein are to be construed as a representation about the suitability of any Product for the particular application of Buyer or user or as an inducement to infringe any patent or other intellectual property right. Buyer is responsible to determine the applicability of such information and recommendations and the suitability of any Product for its own particular purpose, and to ensure that its intended use of the Product does not infringe any intellectual property rights.

The Product may be or become hazardous. The Buyer should obtain Material Safety Data Sheets and Technical Data Sheets from Huntsman containing detailed information on Product hazards and toxicity, together with proper shipping, handling and storage procedures for the Product, and should comply with all applicable governmental laws, regulations and standards relating to the handling, use, storage, distribution and disposal of, and exposure to the Product. Buyer shall also take all steps necessary to adequately inform, warn and familiarize its employees, agents, direct and indirect customers and contractors who may handle or be exposed to the Product of all hazards pertaining to and proper procedures for safe handling, use, storage, transportation and disposal of and exposure to the Product, and the containers or equipment in which the Product may be handled, shipped or stored.

Uralane is a registered trademark of Huntsman LLC or an affiliate thereof in one or more, but not all countries.

© 2015 Huntsman Advanced Materials Inc.

Main Offices:

Huntsman Corporation
10003 Woodloch Forest Dr

The Woodlands, TX 77380
888-564-9318



Advanced Materials

Technical Datasheet



HUNTSMAN

Enriching lives through innovation

Huntsman Advanced Technology Center

8600 Gosling Rd.

The Woodlands, TX 77381

281-829-7400